



LGU - LINGAYEN

BAC

BID AND AN-MBA COMMITTEE

BID SUPPLEMENT

In reference to Invitation to Bid for the *Procurement of Disaster Response and Rescue Equipment to be delivered at LDRRMO, Lingayen, Pangasinan* with an Approved Budget for the Contract of *Two Million Three Hundred Ten Thousand Five Hundred Pesos (P2,310,500.00) Only* which was published, where certain components and technical specifications has been overlooked when being encoded. Thus, said procurement shall have the following revisions:

FROM	TO
<p>Section III BID DATA SHEET (BDS) Clause 19.3 Section VII Technical Specifications Section VI Schedule of Requirements</p>	<p>Section III BID DATA SHEET (BDS) Clause 19.3 Section VII Technical Specifications Section VI Schedule of Requirements</p>
<p>1 set Vehicular Extrication Device <input checked="" type="checkbox"/> POWER UNIT MGHT 2A PETROL ENGINE DRIVEN HYDRAULIC UNIT WITH 2 ALTERNATING OUTLET, ROLL CAGE Variation: 4495075 HYDRAULIC POWER UNIT High performance, compact hydraulic units for near at hand work MGHT 2A : Mini hydraulic unit driven by a single cylinder 4 stroke petrol engine. Cooling by forced air, starting with pullrope. 98cc, 2.2kW (3hp) at 3600l/min Electronic ignition, starter pull rope, petrol capacity 1.2L, 2 alternating outlets, 2 speeds with integrated pressure relief valves Engine power output 3 HP Oil capacity 2.1 1st stage flow at 150 bar 2 L/min 2nd stage flow at 700 bar 0.65 L/min Dimensions L x W x H (mm) 500 x 320 x 440 Weight 24 kg <input checked="" type="checkbox"/> COMBI CUTTER AND SPREADER Polyvalent combi-tool, designed for rapid intervention <input type="checkbox"/> High strength light alloy unit with antiwear treatment. Can be used in wet conditions The combination hydraulic spreader can cut, spread, pull and crush. <input type="checkbox"/> Tool comprises: <input type="checkbox"/> 1 Double action cylinder. <input type="checkbox"/> 1 Ergonomically shaped control handle with integral safety feature and check valve <input type="checkbox"/> 1 Set of hoses 0.5m long with automatically locking, anti-pollution, HP quick couplers fitted with metal protection stoppers. <input type="checkbox"/> 2 straight, high strength forged steel blades with anti-corrosion treatment. <input type="checkbox"/> 2 Removable ribbed tips. 1 U type holding handle. <input type="checkbox"/> Pressure relief valve for hose on coupler end <input type="checkbox"/> Option: Chains set CCMR 2-10 C Operating pressure 700 bar Cutting force 950 kN Depth cutting 110 mm Maximum opening 365 mm Maximum spreading force 80kN Dimensions (mm) 787x224x177 Weight 17.8 kg</p>	<p>1 set Vehicular Extrication Device <input checked="" type="checkbox"/> POWER UNIT MGHT 2A PETROL ENGINE DRIVEN HYDRAULIC UNIT WITH 2 ALTERNATING OUTLET, ROLL CAGE Variation: 4495075 HYDRAULIC POWER UNIT High performance, compact hydraulic units for near at hand work MGHT 2A : Mini hydraulic unit driven by a single cylinder 4 stroke petrol engine. Cooling by forced air, starting with pullrope. 98cc, 2.2kW (3hp) at 3600l/min Electronic ignition, starter pull rope, petrol capacity 1.2L, 2 alternating outlets, 2 speeds with integrated pressure relief valves Engine power output 3 HP Oil capacity 2.1 1st stage flow at 150 bar 2 L/min 2nd stage flow at 700 bar 0.65 L/min Dimensions L x W x H (mm) 500 x 320 x 440 Weight 24 kg <input checked="" type="checkbox"/> COMBI CUTTER AND SPREADER Polyvalent combi-tool, designed for rapid intervention <input type="checkbox"/> High strength light alloy unit with antiwear treatment. Can be used in wet conditions The combination hydraulic spreader can cut, spread, pull and crush. <input type="checkbox"/> Tool comprises: <input type="checkbox"/> 1 Double action cylinder. <input type="checkbox"/> 1 Ergonomically shaped control handle with integral safety feature and check valve <input type="checkbox"/> 1 Set of hoses 0.5m long with automatically locking, anti-pollution, HP quick couplers fitted with metal protection stoppers. <input type="checkbox"/> 2 straight, high strength forged steel blades with anti-corrosion treatment. <input type="checkbox"/> 2 Removable ribbed tips. 1 U type holding handle. <input type="checkbox"/> Pressure relief valve for hose on coupler end <input type="checkbox"/> Option: Chains set CCMR 2-10 C Operating pressure 700 bar Cutting force 950 kN Depth cutting 110 mm Maximum opening 365 mm Maximum spreading force 80kN Dimensions (mm) 787x224x177 Weight 17.8 kg</p>

Head of Procuring Entity

MON LEONILDO N. BATAOG
 Municipal Mayor

Chairman

JOAN LIDIE B. LOPEZ, LIL MOM
 Municipal Civil Registrar

Vice-Chairman

ROBERTO DEL SYLUM
 Municipal Administrator

BAC Members

JEANIE RAYSA N. GOMEZ
 Municipal Budget Officer

ATTY. DOMINIQUE C. EVANGELISTA
 Municipal Legal Officer

RAUL A. UNISON
 Chief Administrative Officer

ENGR. EDSON V. CANILLAS
 Municipal Assessor

JACK WILCO PAUL P. COJALA, III
 MAOC

Technical Working Group

LARRY B. FLORES
 Municipal General Services Officer

ENGR. JOHN INESTER A. TAPIA
 Municipal Engineer

WILSON S. GURAPOS
 Municipal Accountant

BAC Secretariat

ARMANDO I. BERNARDO
 Market Supervisor IV - HEAD

STARON S. SIRON
 Administrative Officer IV

ARWANVY GARCIA M. DE GUZMAN
 Administrative Officer II

CEZAR JAY B. FERNANDEZ
 Security Officer II

AFISA B. GARCIA
 Revenue Collection Clerk II



<p>√ COMBI CUTTER AND SPREADER Polyvalent combi-tool, designed for rapid intervention <input type="checkbox"/> High strength light alloy unit with antiwear treatment. Can be used in wet conditions The combination hydraulic spreader can cut, spread, pull and crush. <input type="checkbox"/> Tool comprises: <input type="checkbox"/> 1 Double action cylinder. <input type="checkbox"/> 1 Ergonomically shaped control handle with integral safety feature and check valve <input type="checkbox"/> 1 Set of hoses 0.5m long with automatically locking, anti-pollution, HP quick couplers fitted with metal protection stoppers. <input type="checkbox"/> 2 straight, high strength forged steel blades with anti-corrosion treatment. <input type="checkbox"/> 2 Removable ribbed tips. 1 U type holding handle. <input type="checkbox"/> Pressure relief valve for hose on coupler end <input type="checkbox"/> Option: Chains set CCMR 2-10 C Operating pressure 700 bar Cutting force 950 kN Depth cutting 110 mm Maximum opening 365 mm Maximum spreading force 80kN Dimensions (mm) 787x224x177 Weight 17.8 kg</p> <p>√ HOSE TWINNED HYDRAULIC HOSE LGT 10M 2FH10T-BL/R BLACK/RED Variation: 4495130 Paired thermoplastic hoses Relief valve on coupler end Hose operating pressure 700 bar Hose bursting pressure 2800 bar Safety coefficient: 4/1 Length: 10 meters</p> <p>√ RAM Made of hardened high strength light alloy Can be used in wet conditions <input type="checkbox"/> 1 Double action cylinder <input type="checkbox"/> 1 Ergonomically shaped control handle with integral safety device and piloting check valves <input type="checkbox"/> 1 Set of 0.5 meter long hoses, automatic locking antipollution. HP quick action couplers with metal protection plugs. Universal swivel fitting Pressure relief valve for hose on coupler end option: Horizontal control handle support Max. force on first piston : 260 kN Max. force on second piston : 119 kN Max. force on third piston : - Stroke A : 575 mm Minimum length B : 515 mm Maximum length C : 1090 mm Weight : 15.45 kg Dimensions (mm) B x H x D : 515 x 316 x 178 Working oil : 465 cc Compliance EN 13204 TR : TR 260/316-119/259-15.45 Operating pressure : 700 bar</p>	<p>√ COMBI CUTTER AND SPREADER Polyvalent combi-tool, designed for rapid intervention <input type="checkbox"/> High strength light alloy unit with antiwear treatment. Can be used in wet conditions The combination hydraulic spreader can cut, spread, pull and crush. <input type="checkbox"/> Tool comprises: <input type="checkbox"/> 1 Double action cylinder. <input type="checkbox"/> 1 Ergonomically shaped control handle with integral safety feature and check valve <input type="checkbox"/> 1 Set of hoses 0.5m long with automatically locking, anti-pollution, HP quick couplers fitted with metal protection stoppers. <input type="checkbox"/> 2 straight, high strength forged steel blades with anti-corrosion treatment. <input type="checkbox"/> 2 Removable ribbed tips. 1 U type holding handle. <input type="checkbox"/> Pressure relief valve for hose on coupler end <input type="checkbox"/> Option: Chains set CCMR 2-10 C Operating pressure 700 bar Cutting force 950 kN Depth cutting 110 mm Maximum opening 365 mm Maximum spreading force 80kN Dimensions (mm) 787x224x177 Weight 17.8 kg</p> <p>√ HOSE TWINNED HYDRAULIC HOSE LGT 10M 2FH10T-BL/R BLACK/RED Variation: 4495130 Paired thermoplastic hoses Relief valve on coupler end Hose operating pressure 700 bar Hose bursting pressure 2800 bar Safety coefficient: 4/1 Length: 10 meters</p> <p>√ RAM Made of hardened high strength light alloy Can be used in wet conditions <input type="checkbox"/> 1 Double action cylinder <input type="checkbox"/> 1 Ergonomically shaped control handle with integral safety device and piloting check valves <input type="checkbox"/> 1 Set of 0.5 meter long hoses, automatic locking antipollution. HP quick action couplers with metal protection plugs. Universal swivel fitting Pressure relief valve for hose on coupler end option: Horizontal control handle support Max. force on first piston : 260 kN Max. force on second piston : 119 kN Max. force on third piston : - Stroke A : 575 mm Minimum length B : 515 mm Maximum length C : 1090 mm Weight : 15.45 kg Dimensions (mm) B x H x D : 515 x 316 x 178 Working oil : 465 cc Compliance EN 13204 TR : TR 260/316-119/259-15.45 Operating pressure : 700 bar <i>One (1) year warranty with free services on parts including replacement if necessary</i></p>
<p>1 Set Scuba Diving Suits Scuba Diving Suits Minimum Requirements/Specifications: √ Diving Mask & Snorkel</p>	<p>1 Set Scuba Diving Suits Scuba Diving Suits Minimum Requirements/Specifications: √ Diving Mask & Snorkel</p>




Republic of the Philippines
MUNICIPALITY OF LINGAYEN
Province of Pangasinan


<p>Malaga single-frame mask with Asian fit Super low volume and liquid silicon Black silicon frame With Mask box & Clear snorkel black</p> <p>✓ Wet Suit * 1 MM Skin Suit all black with smooth skin chest slanted back zipper *</p> <p>✓ Diving Gloves Great Combination of Warmth and Dexterity wear resistance and dexterity Adjustable Velcro wrist closure</p> <p>Suede-like Amara (Synthetic Leather)</p> <p>✓ Low Cut Booties 3MM Low cut booties</p> <p>✓ Diving Fins New Wave cutter open heel fins Size: M/L</p> <p>✓ BCD Jacket BCD Jacket with padded neck collar 3 dump valves chest strap waist strap Velcro type with rear adjustment zipper on both pockets quick release system</p> <p>✓ 1st Stage Regulator QR 3 1st Stage Yoke standard piston</p> <p>✓ 2nd Stage Regulator Standard and stage unbalance no adjustment with hose</p> <p>✓ Octopus Basic octopus no adjustment yellow cover with 40" yellow hose</p> <p>✓ Combo Depth Pressure Gauge Combo depth/ Pressure gauge small size double reading BAR/PSI</p> <p>✓ Oxygen Tank 80 c.u. ft tank with DIN/YOKE convertible tank valve 3000 PSI</p>	<p>Malaga single-frame mask with Asian fit Super low volume and liquid silicon Black silicon frame With Mask box & Clear snorkel black</p> <p>✓ Wet Suit * 1 MM Skin Suit all black with smooth skin chest slanted back zipper *</p> <p>✓ Diving Gloves Great Combination of Warmth and Dexterity wear resistance and dexterity Adjustable Velcro wrist closure</p> <p>Suede-like Amara (Synthetic Leather)</p> <p>✓ Low Cut Booties 3MM Low cut booties</p> <p>✓ Diving Fins New Wave cutter open heel fins Size: M/L</p> <p>✓ BCD Jacket BCD Jacket with padded neck collar 3 dump valves chest strap waist strap Velcro type with rear adjustment zipper on both pockets quick release system</p> <p>✓ 1st Stage Regulator QR 3 1st Stage Yoke standard piston</p> <p>✓ 2nd Stage Regulator Standard and stage unbalance no adjustment with hose</p> <p>✓ Octopus Basic octopus no adjustment yellow cover with 40" yellow hose</p> <p>✓ Combo Depth Pressure Gauge Combo depth/ Pressure gauge small size double reading BAR/PSI</p> <p>✓ Oxygen Tank 80 c.u. ft tank with DIN/YOKE convertible tank valve 3000 PSI</p> <p><i>One (1) year warranty with free services on parts including replacement if necessary</i></p>
---	--

Issued this 7th day of September 2022 at Lingayen, Pangasinan.

Prepared by:


ARNULFO S. BERNARDO
Head, BAC Secretariat

Noted by:


JOAN JUDE R. LOPEZ, LLB, MDM
BAC Chairperson